



APPLICATION
TRACTOR

DRIVE WHEEL TYRES

R-2

- Extra deep tread specially designed to get excellent traction on wet and sticky soil with excellent self cleaning properties, preventing mud clogging between the lugs.
- Sidewall rubber preventing weather cracking.
- Tough tread compound to resist fast wear.



SIZE	PATTERN	PLY RATING	RIM WIDTH	TT or TL	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
					inch	mm	inch	mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi	kmph		mph	
18.4-30	TR-2	8	16.0	TT	465	18.3	1580	62.2	711	28.0	4724	186.0	80	100	2184	4805	1.4	20	135	A8/40kmph	A8/25mph
18.4-34	TR-2	8	16.0	TT	465	18.3	1682	66.2	762	30.0	5029	198.0	80	100	2304	5069	1.4	20	137	A8/40kmph	A8/25mph
	TR-2	12	16.0	TT	465	18.3	1682	66.2	762	30.0	5029	198.0	80	100	3090	6798	2.3	33	147	A8/40kmph	A8/25mph