

IRRIGATION DRIVE

R-1 TYRES

- Designed for irrigation service with minimal soil compaction & excellent wear.
- Long service life thanks to the use of a wear resistant tread compound.



SIZE	PATTERN	PLY RATING	RIM WIDTH inch	TT or TL	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
11.2-24	AGRI ND-2	6	10.0	TT	284	11.2	1105	43.5	508	20.0	3200	126.0	26	33	825	1815	1.3	18	101	A6/30kmph	A6/20mph
	AGRI ND-2	6	10.0	TL	284	11.2	1105	43.5	508	20.0	3200	126.0	26	33	825	1815	1.3	18	101	A6/30kmph	A6/20mph
	AGRI ND-2	8	10.0	TT	284	11.2	1105	43.5	508	20.0	3200	126.0	26	33	900	1980	1.3	18	104	A6/30kmph	A6/20mph
11.2-24	AGRI ND-2	8	10.0	TL	284	11.2	1105	43.5	508	20.0	3200	126.0	26	33	900	1980	1.3	18	104	A6/30kmph	A6/20mph
	IR-007	4	10.0	TT	284	11.2	1105	43.5	508	20.0	3200	126.0	26	33	750	1650	1.3	18	98	A6/30kmph	A6/20mph
12.4-24	IR-007	4	10.0	TL	284	11.2	1105	43.5	508	20.0	3200	126.0	26	33	750	1650	1.3	18	98	A6/30kmph	A6/20mph
	IR-005	6	11.0	TT	315	12.4	1170	46.1	508	20.0	3200	126.0	27	34	1100	2420	1.4	20	112	A6/30kmph	A6/20mph
14.9-24	IR-005	6	11.0	TL	315	12.4	1170	46.1	508	20.0	3200	126.0	27	34	1100	2420	1.4	20	112	A6/30kmph	A6/20mph
	AGRI ND-2	6	13.0	TT	378	14.9	1265	49.8	584	23.0	3658	144.0	30	38	1485	3267	1.6	23	122	A6/30kmph	A6/20mph
	AGRI ND-2	6	13.0	TL	378	14.9	1265	49.8	584	23.0	3658	144.0	30	38	1485	3267	1.6	23	122	A6/30kmph	A6/20mph
	AGRI ND-2	8	13.0	TT	378	14.9	1265	49.8	584	23.0	3658	144.0	30	38	1620	3564	1.6	23	125	A6/30kmph	A6/20mph
	AGRI ND-2	8	13.0	TL	378	14.9	1265	49.8	584	23.0	3658	144.0	30	38	1620	3564	1.6	23	125	A6/30kmph	A6/20mph
	IR-007	4	13.0	TT	378	14.9	1265	49.8	584	23.0	3658	144.0	30	38	1250	2750	1.6	20	116	A6/30kmph	A6/20mph
	IR-007	4	13.0	TL	378	14.9	1265	49.8	584	23.0	3658	144.0	30	38	1250	2750	1.6	20	116	A6/30kmph	A6/20mph
	IR-007	6	13.0	TT	378	14.9	1265	49.8	584	23.0	3658	144.0	30	38	1350	2970	1.4	20	119	A6/30kmph	A6/20mph
	IR-007	6	13.0	TL	378	14.9	1265	49.8	584	23.0	3658	144.0	30	38	1350	2970	1.4	20	119	A6/30kmph	A6/20mph
	IR-005	4	13.0	TT	378	14.9	1265	49.8	584	23.0	3658	144.0	29	36	1250	2750	1.4	20	116	A6/30kmph	A6/20mph
11.2-38	IR-005	4	13.0	TL	378	14.9	1265	49.8	584	23.0	3658	144.0	29	36	1250	2750	1.4	20	116	A6/30kmph	A6/20mph
	IR-005	6	13.0	TT	378	14.9	1265	49.8	584	23.0	3658	144.0	29	36	1350	2970	1.4	20	119	A6/30kmph	A6/20mph
	IR-005	6	13.0	TL	378	14.9	1265	49.8	584	23.0	3658	144.0	29	36	1350	2970	1.4	20	119	A6/30kmph	A6/20mph
	AGRI ND-2	6	10.0	TT	284	11.2	1463	57.6	693	27.3	4343	171.0	29	36	1425	3135	1.6	23	121	A6/30kmph	A6/20mph
	AGRI ND-2	6	10.0	TL	284	11.2	1463	57.6	693	27.3	4343	171.0	29	36	1425	3135	1.8	26	121	A6/30kmph	A6/20mph
	AGRI ND-2	8	10.0	TT	284	11.2	1463	57.6	693	27.3	4343	171.0	29	36	1555	3421	2.1	30	120	A6/30kmph	A6/20mph
	AGRI ND-2	8	10.0	TL	284	11.2	1463	57.6	693	27.3	4343	171.0	29	36	1555	3421	2.1	30	120	A6/30kmph	A6/20mph
	IR-007	6	10.0	TT	284	11.2	1463	57.6	693	27.3	4343	171.0	29	36	1285	2827	1.8	26	117	A6/30kmph	A6/20mph
11.2-38	IR-007	6	10.0	TL	284	11.2	1463	57.6	693	27.3	4343	171.0	29	36	1285	2827	1.8	26	117	A6/30kmph	A6/20mph
	IR-007	8	10.0	TT	284	11.2	1463	57.6	693	27.3	4343	171.0	29	36	1380	3036	2.1	30	120	A6/30kmph	A6/20mph
	IR-007	8	10.0	TL	284	11.2	1463	57.6	693	27.3	4343	171.0	29	36	1380	3036	2.1	30	120	A6/30kmph	A6/20mph
	IR-007	8	10.0	TL	284	11.2	1463	57.6	693	27.3	4343	171.0	29	36	1380	3036	2.1	30	120	A6/30kmph	A6/20mph

Tolerances: O.D. ± 2.5% - S.W. ± 2.5% - RC ± 2.5%