



APPLICATION  
TRACTOR  
4X4



# ROW CROP RADIAL TYRES

## 90 & 95 SERIES

- Round shoulders minimize influence on the crop roots.
- Optimum lug shape & angle provide an excellent grip.
- Long service life thanks to the use of a wear resistant tread compound.



SIZE	PATTERN	RIM WIDTH		TT or TL	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY				INFLATION PRESSURE		LOAD INDEX	SPEED	
		REC	ALT		mm	inch	mm	inch	mm	inch	mm	32nds	25 KMPH MAX LOAD		30 KMPH MAX LOAD		bar	psi	kmph	mph			
		kg	lbs		kg	lbs	bar	psi	kmph	mph													
210/95 R-32 8.3 R-32 120 A8 /B	RC-999	W 8	W 7	TL	214	8.4	1213	47.8	559	22.0	3658	144.0	41	51	1400	3080	1400	3080	2.5	36	120	B/50kmph	B/30mph
230/95 R-32 13.6 R-24 125 A8 /B	RC-999	W 8	W 7	TL	228	9.0	1251	49.3	584	23.0	3759	148.0	44	55	1800	3960	1800	3960	4.1	58	128	B/50kmph	B/30mph
270/95 R-32 14.9 R-24 136 A8 /B	RC-999	W 8	W 9 W 10	TL	275	10.8	1327	52.2	609	24.0	5004	197.0	44	55	2240	4928	2240	4928	4.1	58	136	B/50kmph	B/30mph
230/95R-36 9.5 R-36 124 A8 /B	RC-999	W 8	W 7	TL	228	9.0	1352	53.2	609	24.0	4064	160.0	42	53	1900	4180	1900	4180	4.1	58	130	B/50kmph	B/30mph
270/95 R-36 11.2 R-38 140 A8 /B	UNDER DEVELOPMENT																						
270/95 R-38 11.2 R-36 140 A8 /B	RC-999	W 8	W 9 W 10	TL	264	10.3	1479	58.2	686	27.0	4445	175.0	45	56	2505	5511	2505	5511	4.1	58	140	B/50kmph	B/30mph
230/95 R-44 9.5 R-44 134 A8 /B	RC-999	W 8	W 7	TL	228	9.0	1556	61.3	737	29.0	4699	185.0	44	55	2120	4664	2120	4664	4.1	58	134	B/50kmph	B/30mph
270/95 R-44 9.5 R-44 134 A8 /B	RC-999	W 8	W 9 W 10	TL	275	10.8	1632	64.3	762	30.0	4902	193.0	50	62	2650	5830	2650	5830	4.1	58	142	B/50kmph	B/30mph
300/95 R-46 12.4 R-46 148 A8 /B	RC-999	W 8	W 9 W 11	TL	305	12.0	1737	68.3	813	32.0	5207	205.0	46	57	3157	6945	3157	6945	4.1	58	148	B/50kmph	B/30mph
380/95 R-46 14.9 R-46 148 A8 /B	UNDER DEVELOPMENT																						
230/95 R-48 9.5 R-48 136 A8 /B	RC-999	W 8	W 7	TL	228	9.0	1657	65.2	787	30.1	4978	196.0	45	56	2240	4928	2240	4928	4.1	58	136	B/50kmph	B/30mph
270/95 R-48 11.2 R-48 144 A8 /B	RC-999	W 8	W 9 W 10	TL	275	10.8	1733	68.2	812	32.0	5257	207.0	49	61	2800	6160	2800	6160	4.1	58	144	B/50kmph	B/30mph
300/95 R-52 11.2 R-48 144 A8 /B	RC-999	W 10	W 9 W 11	TL	305	12	1892	75.0	889	35.0	5664	223.0	52	65	3457	7605	3457	7605	4.1	58	151	B/50kmph	B/30mph